

http://www.samaterials.com

Stanford Advanced Materials

We not only sell products, we provide satisfactions. 72 Fairbanks Suite 100, Irvine, CA 92618, USA Tel: (949) 407-8904 Fax: (949) 812-6690

> Current Version: 2.0 Revision Date: Sep 5, 2012

Material Safety Data Sheet

Identity: Bismuth

Formula: Bi

SECTION I - GENERAL INFORMATION

Manufacturer: <u>Stanford Advanced Materials</u> (SAM)

The information below is believed to be accurate and represents the best information available to SAM. However, SAM makes no warranty, expressed or implied with respect to such information and assumes no liability resulting from its use.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Molecular weight: 208.98

CAS #	OSHA PEL	ACGIH TLV	%
7440-69-9	N/A	N/A	100

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Physical States: Solid

Boiling Point: 1420.00 to 1560.00 ℃ Melting Point: 271.30 ℃ Evaporation Rate: N/A Solubility in water: Insoluble Vapor Pressure: (vs. air or mm hg): 1 mm at 1020.0 $^{\circ}$ C Vapor Density: (vs. air =1): No data Specific Gravity: (water = 1) 9.8 gm/cc Percent Volatile: N/A

Appearance and odor: Gray, soft, brittle, bright metallic luster powder; no odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA:

Flash Point: N/A Method Used: Flammable solid

Explosive Limits: LEL:N/A UEL: N/A

Method Used:

Extinguishing Media: Use suitable extinguishing agent for surrounding material and type of fires.



72 Fairbanks Suite 100, Irvine, CA 92618, USA Tel: (949) 407-8904 Fax: (949) 812-6690

Special Fire Fighting Procedures:

Firefighters must wear full face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.

Unusual Fire and Explosion Hazards:

Flammable when exposed to flame. May react with acid or acid fumes to emit toxic fumes. May react with $[Bi(OH)_3 + Al(OH_3)]$, co precipitated and hydrogen produces spontaneously flammable product.

SECTION V - REACTIVITY DATA

Stability: Stable Conditions to Avoid (stability): None Incompatibility: Aluminum, acids, chlorine, BrF₃, NOF NH₄NO₃, IF₃, HNO₃ HC10₄.

Hazardous Decomposition or Byproducts: Bismuth, oxides of bismuth and hydrogen. *Hazardous Polymerization:* Will not occur. *Conditions to avoid (hazardous polymerization): None*

SECTION VI - HEALTH HAZARD DATA

Routes of entry: Inhalation? Yes Skin? No Eyes? No Ingestion? Yes Other? No

Health Hazards (Acute and Chronic):

Inhalation:

Acute: POISON. May be a nuisance dust causing respiratory irritation. May cause fould breath metallic taste and gingivitis.

Chronic: May affect the function of the liver and the kidneys.

Ingestion:

Acute: POISON. May cause malaise, albuminuria, diarrhea, skin reactions, stomatitis,, headache, fever, rheumatic pain, and a black line may form on gums in the mouth.

Chronic: May affect the function of the liver and the kidneys. May cause anemia, black line may form on the gums and ulcerative stomatitis.

Skin: Acute: May cause irritation.. Chronic: May cause dermatitis.

Eye: Acute: May cause irritation. Chronic: No chronic health effects recorded.

Target Organs:



Stanford Advanced Materials

We not only sell products, we provide satisfactions.

http://www.samaterials.com

72 Fairbanks Suite 100, Irvine, CA 92618, USA Tel: (949) 407-8904 Fax: (949) 812-6690

Carcinogenicity: NTP? IARC Monographs?

OSHA Regulated?

Medical Conditions Aggravated by Exposure:

Emergency and First Aid Procedures:

Inhalation: Remove victim to fresh air, keep warm and quiet, and give oxygen if breathing is difficult; seek medical attention

- *Ingestion:* Give 1-2 glasses of milk or water and induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth to an unconscious person
- *Skin:* Remove contaminated clothing, brush material off skin, wash affected area with mild soap and water, and seek medical attention if symptoms persist
- *Eye:* Flush eyes with lukewarm water, lifting upper and lower eyelids for at least 15 minutes and seek medical attention

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case material is released or spilled:

Wear appropriate respiratory and protective equipment specified in section VIII. Isolate spill area, provide ventilation and extinguish sources of ignition. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust.

Waste disposal method:

Dispose of in accordance with state, local, and federal regulations.

Hazard Label Information:

Store in cool, dry area and in tightly sealed container. Wash thoroughly after handling.

SECTION VIII - CONTROL MEASURES

Protective Equipment Summary (Hazard Label Information):

NIOSH approved respirator, impervious gloves, safety glasses, clothes to prevent contact.

Ventilation:

Local Exhaust: To maintain concentration at low exposure levels. Mechanical (General): Recommended.

Work/Hygienic/Maintenance Practices:

Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating or smoking. Do not blow dust off clothing or skin with compressed air.

Please be advised that N/A can either mean Not Applicable or No Data Has Been Established