

http://www.samaterials.com

Stanford Advanced Materials

We not only sell products, we provide satisfactions. 72 Fairbanks Suite 100, Irvine, CA 92618, USA Tel: (949) 407-8904 Fax: (949) 812-6690

> Current Version: 2.0 Revision Date: Sep 5, 2012 Revision Date:

Material Safety Data Sheet

Identity: Magnesium Silicide

Formula: Mg2Si

SECTION I - GENERAL INFORMATION

Manufacturer: Stanford Advanced Materials (SAM)

The information below is believed to be accurate and represents the best information available to SAM. However, SAM makes no warranty, expressed or implied with respect to such information and assumes no liability resulting from its use.

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Molecular weight: 76.70

CAS #	OSHA PEL	ACGIH TLV	%
22831-39-6	N/A	N/A	0-100

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Physical States: Solid

Boiling Point: N/A Melting Point: 1085.00 – 1102.00 °C Rate: N/A Solubility in water: Decomposes in hot water Vapor Pressure (vs. air or mmHg): N/A Specific Gravity: 1.94 gm/cc Evaporation Flash Point: N/A

Appearance and odor: Blue powder, no odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA:

Method Used: Non-flammable

Explosive Limits: LEL: N/A

UEL: N/A

Extinguishing Media: Use suitable extinguishing agent for surrounding material and type of fire

Special Fire Fighting Procedures:

Firefighters must wear full face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. Fumes from fire are hazardous. Isolate runoff to prevent environmental pollution.

Unusual Fire and Explosion Hazards:

DANGEROUS WHEN WET. Decomposed on heating above $500 \,^{\circ}$ in water and hydrochloric acid. May also emit toxic fumes of magnesium oxides.

Stanford Advanced Materials

We not only sell products, we provide satisfactions. 72 Fairbanks Suite 100, Irvine, CA 92618, USA Tel: (949) 407-8904 Fax: (949) 812-6690

http://www.samaterials.com

SECTION V - REACTIVITY DATA

Stability: Stable Conditions to Avoid (stability): None Incompatibility: Water and hydrochloric acid

Hazardous Decomposition or Byproducts: Oxides of magnesium *Hazardous Polymerization:* Will not occur *Conditions to avoid (hazardous polymerization):* None

SECTION VI - HEALTH HAZARD DATA

Signs and Symptoms of Overexposure:

Inhalation: May cause cough, mucous production, shortness of breath, nausea, muscular weakness, lethargy, hypotension, sinus irritation and cardiac arrest *Ingestion:* May cause gastrointestinal disturbances *Skin:* May cause redness, itching, and inflammation *Eye:* May cause redness, itching, swelling, watering and/or burning

Health Hazards (Acute and Chronic):

Inhalation: Acute: May cause irritation and metal fume fever Chronic: May cause kidney damage and fibrogenic effects on the lungs

Ingestion: Acute: May cause irritation Chronic: No chronic health effects recorded

Skin: Acute: May cause irritation Chronic: No chronic effects recorded

Eye: Acute: May cause severe irritation Chronic: No chronic health effects recorded

Target Organs:May affect kidneys and lungsCarcinogenicity:NTP?NoIARC Monographs? NoOSHA Regulated? NoMedical Conditions Aggravated by Exposure:Pre-existing respiratory disorders

Emergency and First Aid Procedures:

Inhalation: Remove victim to fresh air, keep warm and quiet, and give oxygen if breathing is difficult; seek medical attentionIngestion: Give 1-2 glasses of milk or water and induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth to an unconscious person



http://www.samaterials.com

- *Skin:* Remove contaminated clothing, brush material off skin, wash affected area with mild soap and water, and seek medical attention if symptoms persist
- *Eye:* Flush eyes with lukewarm water, lifting upper and lower eyelids for at least 15 minutes and seek medical attention

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case material is released or spilled:

Wear appropriate respiratory and protective equipment specified in section VIII. Isolate spill area, provide ventilation and extinguish sources of ignition. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for proper disposal. Take care not to raise dust.

Waste disposal method:

Dispose of in accordance with state, local, and federal regulations.

Hazard Label Information:

Store in cool, dry area and in tightly sealed container. Wash thoroughly after handling.

SECTION VIII - CONTROL MEASURES

Protective Equipment Summary (Hazard Label Information):

NIOSH approved respirator, impervious gloves, safety glasses, clothes to prevent contact.

Ventilation:

Local Exhaust: To maintain concentration at low exposure levels. Mechanical (General): Recommended.

Work/Hygienic/Maintenance Practices:

Implement engineering and work practice controls to reduce and maintain concentration of exposure at low levels. Use good housekeeping and sanitation practices. Do not use tobacco or food in work area. Wash thoroughly before eating or smoking. Do not blow dust off clothing or skin with compressed air.

Please be advised that N/A can either mean Not Applicable or No Data Has Been Established