



SAFETY DATA SHEET

Version 3.0 Revision Date 09/04/2017

1. PRODUCT AND COMPANY IDENTIFICATION

1.1Product identifiers

Product name : Tungsten

Brand : SAM

CAS-No. : 7440-33-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Stanford Advanced

Company : Materials

23661 Birtcher Dr. Lake Forest, CA 92630

USA

Telephone : +1 (949) 407-8904Fax : +1 (949) 812-6690

1.4 Emergency telephone number

Emergency Phone # : +1 (949) 407-8904

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable solids (Category 1), H228 Skin irritation (Category 2), H315 Eye irritation (Category 2A), H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram

(1)

Signal word Danger

Hazard statement(s)

H228 Flammable solid. H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for

extinction.

2.3Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1Substances

Formula : W

Molecular weight : 183.84 g/mol CAS-No. : 7440-33-7 EC-No. : 231-143-9

Hazardous components

Component	Classification	Concentration
Tungsten		
	Flam. Sol. 1; Self-heat. 2;	<= 100 %
	H228, H252	

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment

needed No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal. Contain spillage, pick up with an electrically protected vacuum cleaner or by wetbrushing and transfer to a container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Keep in a dry place.

Storage class (TRGS 510): Flammable solid hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL

PROTECTION 8.1 Control parameters

Components with workplace control parameters

Components with workplace control parameters						
Component	CAS-No.	Value	Control	Basis		
			parameters			
Tungsten	7440-33-7	TWA	5.000000	USA. ACGIH Threshold Limit Values		
			mg/m3	(TLV)		
	Remarks	Lower Respiratory Tract irritation				
		STEL	10.000000	USA. ACGIH Threshold Limit Values		
			mg/m3	(TLV)		
		Lower Respiratory Tract irritation				
		TWA	5.000000	USA. NIOSH Recommended		
			mg/m3	Exposure Limits		
		ST	10.000000	USA. NIOSH Recommended		
			mg/m3	Exposure Limits		
		TWA	5.000000	USA. ACGIH Threshold Limit Values		
			mg/m3	(TLV)		
		Lower Respiratory Tract irritation				
		varies				
		STEL	10.000000	USA. ACGIH Threshold Limit Values		
			mg/m3	(TLV)		
		Lower Respiratory Tract irritation				
		varies				

TWA	5 mg/m3	USA. NIOSH Recommended Exposure Limits	
ST	10 mg/m3	USA. NIOSH Recommended Exposure Limits	
TWA	5 mg/m3	USA. ACGIH Threshold Limit Values (TLV)	
Lower Re	Lower Respiratory Tract irritation varies		
STEL	10 mg/m3	USA. ACGIH Threshold Limit Values (TLV)	
Lower Re varies	Lower Respiratory Tract irritation varies		
PEL	5 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

boiling range

9.1 Information on basic physical and chemical properties

a) Appearance Form: powder Colour: grey

b) Odourc) Odour Thresholdd) pHNo data availableNo data available

e) Melting point/freezing Melting point/range: 3,410 °C (6,170 °F) - lit. point

f) Initial boiling point and 5,660 °C (10,220 °F) - lit.

g) Flash point Not applicableh) Evaporation rate No data available

i) Flammability (solid, gas) The substance or mixture is a flammable solid with the category 1.

j) Upper/lower flammability or explosive limits No data available

k) Vapour pressure No data availablel) Vapour density No data available

m) Relative density 19.3 g/cm3 at 25 °C (77 °F)

m) Water solubility No data available
 o) Partition coefficient: n- No data available octanol/water

octanol/water
p) Auto-ignition

No data available

q) Decomposition temperature

temperature

No data available

r) Viscosity No data available
 s) Explosive properties No data available
 t) Oxidizing properties No data available

9.2 Other safety information

No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents, Halogens

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Tungsten oxide Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - > 2,000 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - > 5.4 mg/l

(OECD Test Guideline 403)

LD50 Dermal - Rat - male and female - > 2,000 mg/kg

(OECD Test Guideline 402)

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Mild eye irritation (OECD Test Guideline 405)

Respiratory or skin sensitisation

Maximisation Test - Guinea pig

Result: Does not cause skin sensitisation.

(OECD Test Guideline 406)

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified

as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as

a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as

a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available

Reproductive toxicity - Rat - Oral

Effects on Fertility: Post-implantation mortality (e.g., dead and/or resorbed implants per total number of implants).

Specific Developmental Abnormalities: Musculoskeletal system.

No data available

Developmental Toxicity - Rat - Oral

Specific Developmental Abnormalities: Musculoskeletal system.

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: YO7175000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 3089 Class: 4.1 Packing group: II

Proper shipping name: Metal powders, flammable, n.o.s.

Reportable Quantity (RQ):

Poison Inhalation Hazard: No

IMDG

UN number: 3089 Class: 4.1 Packing group: II EMS-No: F-G, S-G

Proper shipping name: METAL POWDER, FLAMMABLE, N.O.S.

IATA

UN number: 3089 Class: 4.1 Packing group: II

Proper shipping name: Metal powder, flammable, n.o.s.

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

CAS No

Revision Date

SARA 311/312 Hazards

Fire Hazard

Massachusetts Right To Know Components

	OAO-NO.	itevision Date
Tungsten	7440-33-7	1994-04-01
Pennsylvania Right To Know Components		

CAS-No. Revision Date Tungsten 7440-33-7 1994-04-01

New Jersey Right To Know Components

 CAS-No.
 Revision Date

 Tungsten
 7440-33-7
 1994-04-01

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Flam. Sol. Flammable solids H228 Flammable solid.

H252 Self-heating in large quantities; may catch fire.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

HMIS Rating

Health hazard: 2 Chronic Health Hazard:

Flammability: 3 Physical Hazard 3

NFPA Rating

Health hazard: 2
Fire Hazard: 3
Reactivity Hazard: 3

Further information

This material safety data sheet is offered solely for your information, consideration, and investigation. Stanford Advanced Materials provides no warranties, either express or implied, and assumes no responsibility for the accuracy or completeness of the data contained herein.